

RITE DOOR - Metal Doors

ITEM	ITEM DESCRIPTION	This is for basic reference for product information and ordering, for detail description of product, see the product cut sheets.	
0 WOOD OR METAL			
		<i>Specify the door material type you want quoted or ordered</i>	
	W	Wood Door Type	
	M	Metal Door type	
1 ID MARK			
	Enter in the mark id, door or opening # in this field.		
2 QUANTITY			
	Enter in the qty of doors you want to order on this line item.		
3 SERIES			
		<i>Door Series and Models</i>	
	707	Metal Door Series to be used for Polystyrene or Honeycomb Core	
	747	Metal Door Series to be used for Steel Stiffened Core	
	727	Metal Door Series to be used for Temp-Rise Core	
4 CONSTRUCTION			
		<i>Core Construction of the door</i>	
	P	Polystyrene Core	
	H	Honeycomb core	
	T2	Temperature Rise Core 250°	
	T4	Temperature Rise Core 450°	
	S	Steel Stiffened Core	
5 ADDITIONAL INFORMATION			
	L	Lead Lined Core - 1/16" thick Lead	
6 EDGE CONSTRUCTION			
		<i>Hinge and Lock Stile construction of the door</i>	
	N	Door Edge Seam Spot welded and Filled	
	S	Visible Edge Seam - to be used with CURRIEStain Door Product	
7 LABEL			
		<i>Used when a customer requests a fire rated door ((ITS/Warnock Hersey Fire Labeling Authority)</i>	
		Non Rated	
	PP	Positive Pressure Category (20, 45, 60 & 90 Min Rated Doors)	
8 RATING			
		<i>Need to specify when customer is calling out for a fire rated door.</i>	
		Non Rated	
	20	20 Minute Rating	
	45	45 Minute Rating	
	60	60 Minute Rating	
	90	90 Minute Rating	
	180	3 Hour Rating	
9 STEEL TYPE			
		<i>Steel type as requested by the customer</i>	
	CR	Cold Rolled Steel	
	RK	Galvanized (A60 Standard)	
	SS	Stainless (304 #4 Satin finish)	
	A1	CURRIStain (Specify Color) - Deep Oak Wood Grain Embossment	
	HP	High Pressure Laminate	
9A STEEL GAUGE			
		<i>Specify the gauge of steel that you would like</i>	
	18	18 Gauge Steel	
	16	16 Gauge Steel	
	14	14 Gauge Steel - (Not available with CURRIEStain)	
10 FACE TYPE			
		<i>Lite cutout on the door</i>	
	F	Flush	
	FV	Square Lite	
	FNV	Narrow Vision Lite	
	HG	Half Glass	
	FG2	Full Glass Lite with Intermediate Rail (2 Half Glass Cutouts)	
	L	Louver	
		<p>Non Rated Doors - Lites must maintain a min 6" of wood material between any cutouts to maintain warranty on the door.</p> <p>20 & 45 Min Rated Doors - Can have up to 1296 sq inches of visible glass dimensions, but must maintain a min 5" of material between any cutout on the door to maintain fire label.</p> <p>60 & 90 Min Rated Doors - Can have up to 100 sq inches of visible glass dimensions, but must maintain a min 5" of material between any cutout on the door to maintain fire label.</p>	
		Louvers	

11 LITE SIZE & LOCATION ELEVATION	<i>Use the Lite Size & Location Elevation sheet to give the size and location of the lite on the door.</i>	
12 MOULDING / LITE KIT	<i>Trim placed in the lite cutout to hold the glass in the opening</i>	
1	Metal Vision Lite Kit - Square. 3/8" Pocket standard	
2	Metal Vision Lite Kit - Square. 5/8" Pocket standard	
3	Metal Vision Lite Kit - Concealed Square. 3/8", 1/2", & 5/8" Pocket. (Specify)	<i>Please specify pocket size for lite kit if other than standard</i>
9	Metal Vision Lite Kit - Beveled. 3/8" Pocket standard	
10	Metal Vision Lite Kit - Beveled. 9/16" Pocket standard	
13 GLASS TYPE	<i>Factory Installed Glass - Available upon request from the customer</i>	
FIG01	Clear Tempered - Standard for non rated doors - 1/4" thick	<i>All glass comes with glazing tape as required. Rectangular/square glass only. Contact Factory for availability of glazing not listed. Fire rating limitations on glazing may limit availability on some doors. Detail for each glass type available upon request.</i>
FIG02	Filmed Wire - Standard for rated doors - 1/4" thick	
FIG03	Ceramic Filmed Pyran Platinum F - optional - 3/16" thick	
FIG07E	5/8" IGU - Standard for Exterior Applications	
FIG08E	5/8" IGU - Standard for Exterior Applications	
*	FireLite NT & FireLite Plus Available - Factory Quote Only for Metal Doors.	
14 GLASS THICKNESS	<i>Specify the glass thickness you would like to use with you Moulding / Lite Kit</i>	
3/16"	3/16" Thick Glass	
1/4"	1/4" Thick Glass (Standard)	
5/16"	5/16" Thick Glass	
3/8"	3/8" Thick Glass	
*	Other - Specify the glass thickness needed other than what is listed above. - Lite Kit and Glass type must comply with the Fire Label Testing Authority on the door. Contact factory to see if the glass type and lite kit are an approved application	
15/16 WIDTH	<i>Nominal door width before prefit</i>	
FEET	Nominal Feet	
INCHES	Nominal Inches along with Fractional Sizes	
17/18 HEIGHT	<i>Nominal door height before prefit</i>	
FEET	Nominal Feet	
INCHES	Nominal Inches along with Fractional Sizes	
19 THICKNESS	<i>Door Thickness</i>	
4	1 3/4" - Only Available Thickness	
20 HAND	<i>Swing of the door</i>	
R	Right Hand Swing	
L	Left Hand Swing	
RR	Right Hand Reverse Swing	
LR	Left Hand Reverse Swing	
21 BEVEL	<i>Cut on the lock and hinge stile of the door to allow for proper closing of the door</i>	
3/3	3° Bevel on both lock and hinge stile - Use when you have Butt Hinges on the hinge stile of the door	
3L	3° Bevel on the lock stile only, hinge stile is square - Use when you have Continuous Hinges on the hinge stile of the door	
3H	3° Bevel on the hinge stile only, lock stile is square - Use per customer's request only	
0	No bevel on either side of the lock or hinge stile - Door will still be prefit - Use per customer's request only	
FS	Full and Square door - No Bevel or Prefit to the door - Use per customer's request only	
22 FRAME MFG	<i>Identifies the frame manufacturer</i>	<i>Std Undercut</i>
CU	Curries - Will receive Curries standard hardware locations unless otherwise specified	5/8"
C	Ceco - Will receive Ceco standard hardware locations unless otherwise specified	3/4"
A	Amweld - Will receive Amweld standard hardware locations unless otherwise specified	3/4"
M	Mesker - Will receive Mesker standard hardware locations unless otherwise specified	3/4"
S	Steelcraft - Will receive Steelcraft standard hardware locations unless otherwise specified	3/4"
P	Pioneer - Will receive Pioneer standard hardware locations unless otherwise specified	5/8"
SP	Special Locations - Use this code when you have special hardware location - you will need to give locations for the door when placing the order	5/8"
23 SET	<i>Used when pairing doors - Pairs need to be broke up on individual line items. Can not have pairs on the same line.</i>	
	Single Door	
PR	Standard Pair (Same Swing Pair - Opposite Handing)	
DE	Double Egress Pair (Opposite Swing Pair - Same Handing)	
UEP	Unequal Pair (Standard Pairs where the leaves are not the same size)	
UDE	Unequal Double Egress (Double Egress Pairs where the leaves are not the same size)	

- 24 GROUP** < *Indicates when the pair begins and when the pair ends - must be used with lines grouped together*
 > Starting of the Pair
 Ending of the Pair
- 25 HARDWARE SET** *Details out the hardware needed for the door (Locks, Hinges, Closers, Mag Locks, Seal Kit, etc - See Hardware Set Info on following page.*
- 26 SPECIAL HDWE LOC ELEVATION** *This Elevation is to be used when specifying special hardware location other than RITE Door standards.*
- 27 FACE FINISH (METAL)** *Face Finishes for Metal Doors*
- | | | |
|---------------|------------------------------------|--|
| PR6 | Prime 6 Sides (Primed Door Only) | <i>Standard Factory Grey Primer</i> |
| 45E-4W | Prefinished Color - Flambeau Brown | |
| 38E-1W | Prefinished Color - Ivory | |
| 6E-1W | Prefinished Color - Champagne | |
| 10E-2W | Prefinished Color - Salmon | |
| 32D-4M | Prefinished Color - Aqua | |
| 24E-3W | Prefinished Color - Granite | <i>Prefinished / Painted Colors. 10 standard colors available. For custom color match, send sample for color match and approval.</i> |
| 5E-3W | Prefinished Color - Sand | |
| 6E-3W | Prefinished Color - Coral | |
| 40E-3W | Prefinished Color - Almond | |
| 40E-2W | Prefinished Color - Bone | |
| CST | Prefinished Color - Custom color | |
| CS-NAT | CURRIEStain - Natural | |
| CS-WHT | CURRIEStain - Wheat | |
| CS-CSH | CURRIEStain - Cashew | <i>Factory Finished with one of Six Standard Colors. No Color Match Available. Available in Poly Styrene Core Only</i> |
| CS-COC | CURRIEStain - Cocoa | |
| CS-CAB | CURRIEStain - Cabernet | |
| CS-JAV | CURRIEStain - Java | |
| HPL-* | High Pressure Laminate - Color | <i>Specify HPL Manufacturer and HPL Color when ordering</i> |
- 28 UNDERCUT** *The amount of material requested to be subtracted from the bottom of the nominal door height.*
- 5/8"** Standard Undercut - This will be the given undercut unless otherwise indicated by a frame mfg code or specified by the customer
- *** All other undercuts available with the minimum undercut being 1/8" and the maximum undercut being 15/16"
- 29 SPECIAL INSTRUCTIONS** This is for any special instructions that are needed for the door. Not all special instruction request can be accommodated, please contact factory to verify if request is available with the RITE Door - True Wood Door. You can also use this section to specify request for hardware that is not supplied, but will be a prep only

***For Leed Qualifications, please see the Leed Sell Sheet for details on Leed Qualifications for all RITE Door products.**

HOW TO REQUEST A QUOTE/ORDER FOR RITE DOOR PRODUCTS																																					
														NOM WIDTH		NOM HEIGHT																					
LINE ITEM	WOOD (W) OR METAL (M)	ID MARK	QUANTITY	SERIES	CONSTRUCTION	ADDITIONAL INFO	EDGE CONSTRUCTION	LABEL	RATING	VENEER SPECIES / STEEL TYPE	VENEER PLY / STEEL GAGE	FACE TYPE	LITE SIZE / LOC ELEVATION	MOULDING / LITE KIT	GLASS TYPE	GLASS THICKNESS	FEET	INCHES	FEET	INCHES	THICKNESS	HAND	BEVEL	FRAME MFG	SET	GROUP	HARDWARE SET	SPL HDW LOC ELEVATION	PREFINISH (WOOD) / FACE FINISH (METAL)	UNDERCUT							
	0	1	2	3	4	5	6	7	8	9	9A	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28							
SPECIAL INSTRUCTIONS																												29									