

# RITE DOOR ELEVATION FORM – SPECIAL HARDWARE OR LITE ELEVATION

## Elevation Sheet *(To Be Used With Order Form)*

DISTRIBUTOR <span style="background-color: #f39c12; display: inline-block; width: 100px; height: 15px;"></span>	PO # <span style="background-color: #f39c12; display: inline-block; width: 80px; height: 15px;"></span>	JOB NAME <span style="background-color: #f39c12; display: inline-block; width: 150px; height: 15px;"></span>
---	---	--

**COLUMN #26 - Special Hardware Elevation**

SPECIAL HARDWARE ELEVATION #

TOP OF DOOR TO TOP OF HINGE

SPECIAL NOTES

**COLUMN #11 - Face Type / Special Lite Elevation**

ELEVATION #

ELEVATION #

ELEVATION #

ELEVATION #

ELEVATION #

ELEVATION #

- \* 1/4" GLASS THICKNESS IS STANDARD.
- \* PLEASE NOTE IF ANOTHER THICKNESS APPLIES.
- \* REMEMBER TO CHECK FOR LITE / HARDWARE CONFLICTS
- \* ALL SIZES AND LOCATIONS ARE TO VISIBLE GLASS UNLESS STATED OTHERWISE.
- \* STANDARD TOP RAIL LOCATION FOR HG AND FG LITES IS 8" UP TO 7'2".
- \* STANDARD TOP RAIL LOCATION FOR FNV LITES IS 7-3/4" UP TO 7'2", STD. LOCKSTILE LOCATION IS 6-3/4" FOR FNV'S.
- \* STANDARD FV LOCATION IS 65" AFF TO THE CENTERLINE.
- \* STANDARD LOUVER LOCATION IS 12" AFF. ALL LOUVER LOCATIONS WILL BE LOCATED AFF UNLESS STATED OTHERWISE.